

The PostProcess™ DEMI 4000™ series leverages our proprietary patented Submersed Vortex Cavitation technology for revolutionary post-printing efficiencies; combining software, hardware, and chemistry features for optimal resin removal.

- AUTOMAT3D® intelligent software control of energy sources and simplified machine operation.
- Vortex pumping scheme ensures uniform chemistry exposure to finish parts with unprecedented consistency.
- Precision control over temperature and ultrasonic-generated cavitations for accelerated process times.
- Variable energy output to adapt to material and geometry needs results in reduced damage.



### SOFTWARE FEATURES

- Programmable cycle time
- Storable user recipes
- Proprietary Agitation Algorithms
- CONNECT3D® factory automation
- Automatic load/unload sequence

### HARDWARE FEATURES

- Digital interface
- Automated build tray lift
- Chemically compatible pump
- Configurable lift fixture
- Levelling casters for easy installation & setup

### PRODUCT SPECIFICATIONS

#### SIZE

	DEMI 4000 & DEMI 4100* Standard Package	DEMI 4150* Ceramics Package
Envelope:	35" L x 35" W x 25" H 89 cm x 89 cm x 63.5 cm	35" L x 35" W x 25" H 89 cm x 89 cm x 63.5 cm
Machine Footprint:	87" L x 50" W x 88" H 221 cm x 127 cm x 224 cm	87" L x 84" W x 88" H 221 cm x 213 cm x 224 cm
Approximate Weight:	2590 lbs (1174 kg) empty, 4886 lbs (2216 kg) full	2730 lbs (1238 kg) empty, 5100 lbs (2313 kg) full
Lift Capacity:	200 lbs (90 kg)	200 lbs (90 kg)


#### SAFETY FEATURES

- Emergency stop
- Auto power down
- Safety interlocked door
- CSA and UL approvals
- 

#### CONSUMABLES

	DEMI 4000 & DEMI 4100	DEMI 4150
Capacity:	260 gallons (984 liters)	275 gallons (1040 liters)
Detergent:	PLM-403-SUB	PLM-405-SUB

#### PRINT TECHNOLOGIES



#### ELECTRICAL

North America	Europe
DEMI 4000 - 240V 1-phase, 60Hz	DEMI 4000 - 230V, 50Hz, 1-phase + N
DEMI 4100 - 240V, 3-phase, 60Hz	DEMI 4100 - 400V, 50hz, 3-phase

#### POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France  
+33 (0)4 22 32 68 13

\*includes ultrasonics