

HARDWARE FEATURES

- Stainless steel envelope
- Multi-dimensional spray coverage
- In-line strainer
- Sealed, top-loading chamber
- Customizable fixtures available
- Built-in work station
- Casters for easy installation

RESULTING IN...

- + Superior support removal
- + Evenly treated parts
- + Cycle time reduction

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D® platform
- Proprietary *Agitation Algorithms*
- Variable temperature (130-160°F, 54-71°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Preventative maintenance schedules

RESULTING IN...

- + Minimized part breakage
- + Minimal operator intervention
- + Preservation of fine-feature details

PRODUCT SPECIFICATIONS

SIZE AND WEIGHT

Envelope:	16" L x 16" W x 14.5" H (41 cm x 41 cm x 37 cm)
Machine Footprint (closed door):	67" W x 35" D x 67" H (170 cm x 88 cm x 170 cm)
Approx. Weight:	850 lbs. (386 kg) empty 1060 lbs. (481 kg) full

CONSUMABLES

Detergent: PLM-201/202-SPRAY

FACILITIES REQUIREMENTS

- Water in
- Drain out
- Ventilation

ELECTRICAL

US:

- Voltage: 240V 3-Phase
- Amperage: 30A
- Plug: ABB430P9W

EU:

- Voltage: 400V 3-Phase
- Amperage: 15A
- Plug: ABB430P6W

SAFETY FEATURES

- Emergency stop
- Door locks
- Temperature limits
- Auto-interrupt
-  

POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA
info@postprocess.com +1.866.430.5354

POSTPROCESS TECHNOLOGIES INTERNATIONAL

49 Impasse du Hameau, 06250 Mougins, France
+33 (0)4 22 32 68 13

